

Declaration of Performance

Jackofoam® Terra XPS 400

- 1. Unique identification code of the product-type:** NO-JFT400-CPR-02
- 2. Type, batch pr serial number:** Jackofoam® Terra XPS
- 3. Intended use or uses of the construction product:** Thermal insulation products for buildings (XPS)
- 4. Name and contact address of the manufacturer:** BEWI Insulation Norge AS, Box 1410, 1602 Fredrikstad
- 5. Where applicable, name and contact address of the authorised representative:**
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:** AVCP System 3
- 7. Notified Testing Laboratory and tasks performed** Sintef, ID-number 1071 has conducted ITT under system 3.

8. Essential characteristics (EN 13164: 2012+A1:2015)	Performance				Note
Thermal conductivity - Thickness: 0 - 50 mm	$\lambda_D = 0,032$ W/mK				EN 12667
Thermal conductivity - Thickness: 60 - 70 mm	$\lambda_D = 0,035$ W/mK				EN 12667
Thermal conductivity - Thickness: 80 - 100 mm	$\lambda_D = 0,032$ W/mK				EN 12667
Thermal conductivity - Thickness: 120 - 150 mm	$\lambda_D = 0,035$ W/mK				EN 12667
Thermal resistance – Thickness: 100 mm	$R_d=3,13$				(resistance R_D)
Compressive stress at 10% deformation	CS(10) = 400 kPa				ISO 29469
Durability of compressive strength against ageing and degradation, Compressive creep (2%)	CC = 180 kPa				EN 1606
Long term water absorption by immersion	WL(T) 0,7				EN/ISO 16535
Watervapor transmission μ	$\mu = 150$				EN 10456
Tolerances (T1)	Tolerances (mm)		Thickness product (mm)		EN13164 ISO 29466
	-2	+2	< 50		
	-2	+3	$50 \leq d_N \leq 120$		
Tolerances	-2	+8	> 120		EN13164
	Nominal length or width	Length or width	Squareness of length and width	Flatness	
	mm	mm	S_b mm/m	S_{max} mm	
	Less than 1000	± 8	5	7,0	
	1000-2000	± 10	5	14,0	
> 2000 to 4000	± 10	5	28,0		
> 4000	± 10	5	35,0		
Fire class (Reaction to fire)	NPD				-
Continuous glowing combustion	NPD				-
Durability of thermal conductivity against heat, weathering, and ageing/degradation	No changes over time/NPD				-
Freeze-thaw resistance after long term water absorption by total immersion	FTCI = 1%				EN 12091
Release of dangerous substances	NPD (a)				-
Tensile strength perpendicular to faces	NPD				EN 1607

(a) Test method is not available

9. The performance of the product listed above is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer, as noted above.

Signed for and behalf of the manufacturer by:



Svein Tore Larsen, Product Manager
Fredrikstad, 2025.09.19